





**SPECIFICATIONS**

Rated Current:3.0AMP  
 Contact Resistance:30mΩ Max  
 Withstand Voltage:1000V AC/DC  
 Insulation Resistance:1000MΩ Min  
 Operation Temperature:-40°c to +105°c


Contact Material:Copper Alloy  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Resistance To Soldering Heat:  
 245°C±5°C For 5 Second(PBT insulator)



**Ordering Information**

**3511 3 120 A M S XX B W A X**

- No.of Pins  
NPin  
N=120
- Contact Type  
M=Male
- Contact Plating  
G0:Gold Flash  
S0:Gold Flash/Tin  
S1:3U" Gold/Tin  
S2:5U" Gold/Tin  
S3:10U" Gold/Tin  
S4:15U" Gold/Tin  
S5:30U" Gold/Tin
- Contact Material  
B=Brass
- Stream Code



Recommended P.C.B Layout(Top Side)  
 (PCB BOARD TOLERANCE± 0.05)

Dimension antitheses list	
ITEM	A
Standard	4.00

A	AO	2023.03.29	NEW DRAWING	CHANGE	OPERATION	DRAW	Jelly Feng	2023.03.29	SCALE	FIT	<b>JILN</b> ® 深圳市锦凌电子有限公司 SHENZHEN JINLING ELECTRONICS CO.,LTD Tel: 86-755-27483253 Fax: 86-755-2997-5588	PART NO.	35113120AMSXXBWAX	
	REV	DATE	MODIFICATION DESCRIPTION	CHANGE	X.X ±0.30	CHECK			UNIT	mm			TITLE:	欧式插座 公座 180度 带鱼叉 成品系列图
					X.XX ±0.20	APPROVE			SIZE	A4				
					X.XXX ±0.10				SHEET	1/1				
				Angle ±3°				PROJ.	⊕					
				DIM TOL										