







SPECIFICATIONS

Rated Current:3.0AMP
 Contact Resistance:30mΩ Max
 Withstand Voltage:1000V AC/DC
 Insulation Resistance:1000MΩ Min
 Operation Temperature:-40°C to +105°C

Contact Material:Copper Alloy
 Contact Plating:Au or Sn Over Ni
 Insulator Material:Polyester(UL94V-0)
 Resistance To Soldering Heat:
 245°C±5°C For 5 Second(PBT insulator)



Ordering Information

3511 4 128 A M R XX B W A X

- No. of Pins
NPin
N=128
- Contact Type
M=Male
- Contact Plating
G0:Gold Flash
S0:Gold Flash/Tin
S1:3U" Gold/Tin
S2:5U" Gold/Tin
S3:10U" Gold/Tin
S4:15U" Gold/Tin
S5:30U" Gold/Tin
- Contact Material
B=Brass
- Stream Code

Recommended P.C.B Layout(Top Side)
 (PCB BOARD TOLERANCE± 0.05)

Dimension antitheses list	
ITEM	A
Standard	3.00

				OPERATION		DRAW	Jelly Feng	2023.03.29	SCALE	FIT	JILN ® 深圳市锦凌电子有限公司 SHENZHEN JINLING ELECTRONICS CO.,LTD Tel: 86-755-27483253 Fax: 86-755-2997-5588		
				X.X	±0.30				UNIT	mm			
				X.XX	±0.20	CHECK			SIZE	A4	PART NO.		35114128AMRXXBWAX
				X.XXX	±0.10						SHEET		1/1
A0	2023.03.29	NEW DRAWING		Angle	±3°	APPROVE			PROJ.				
REV	DATE	MODIFICATION DESCRIPTION		DIM	TOL								
1	2	3	4	5	6	7	8	9					